



TECHNICAL DATA SHEET



Henkel Consumer Adhesives Inc.
Rocky Hill, CT 06067
Phone 1-800-624-7767
Fax (440) 250-7863
www.henkel.com www.loctiteproducts.com



DESCRIPTION:

Loctite® Aluminum Jelly cleans and brightens aluminum by removing the dull film caused by corrosion from screen doors, window screens and trim. The gel formula is ideal for vertical surfaces. It is easy to use, works fast, washes off with water, will not run and will not drip.

RECOMMENDED FOR:

Brightening weathered aluminum and remove oxidation in minutes.

NOT RECOMMENDED FOR:

New or anodized surfaces.

FEATURES & BENEFITS:

Feature	Benefits
Gel formula.....	Ideal for vertical surfaces
Simply sponge on and rinse off	Easy to use
Water soluble.....	Easy clean-up with water

Item #	Package	Size
1415346	Bottle	8 fl. oz.

DIRECTIONS:

Tools Typically Required:

Brush or sponge.

Safety Precautions:

Well-ventilated area, rubber or plastic gloves.

Preparation:

Wash off surface to remove dirt, oil and grease.

Application:

Apply between 50°F (10°C) and 90°F (32°C). Brush or sponge on liberally. Leave on for 5 minutes. An excessive time period may tend to darken some surfaces. Rinse off with fresh water. Repeat application, if necessary for heavily corroded areas. Use several 5 minute applications rather than one extended application. Rinse after each one.

Clean-up

Water.

STORAGE AND DISPOSAL

Not damaged by freezing. Store above freezing. Use an approved hazardous waste facility for disposal.

LABEL PRECAUTIONS

CAUTION: CONTAINS PHOSPHORIC ACID.

Avoid contact with skin. In case of contact, wash off immediately with water. As an added precaution, wear rubber gloves. In case of eye contact, flush with running water for 15 minutes and get prompt medical attention. If swallowed, do not induce vomiting. Give one or two glasses of water or milk and call a physician. Use with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

Refer to the Material Safety Data Sheet (MSDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
<u>Color:</u>	Pale blue	<u>Application Temperature:</u>	Apply between 50°F (10°C) and 90°F (32°C)
<u>Appearance:</u>	Thick liquid	<u>Odor:</u>	Mildly fruity
<u>Base:</u>	Phosphoric acid	<u>Working Time:</u>	5 minutes
<u>Specific Gravity:</u>	1.06	<u>Clean Up:</u>	Water
<u>VOC Content:</u>	2.2 %		
<u>pH:</u>	2.0		
<u>Viscosity:</u>	2.5 Mcps		