



TECHNICAL DATA SHEET



Henkel Corporation
Professional and Consumer Adhesives
Rocky Hill, CT
Phone 1-800-624-7767
Fax (440) 250-7863
www.henkel.com www.loctiteproducts.com



Item #	Package	Size
431278	Spray Can	10.25 oz.

DESCRIPTION:

Loctite® Silicone Spray Lubricant is a special, high quality lubricating silicone, which can be used to lubricate moving parts, protect surfaces from corrosion and moisture and also to protect locks from freezing.

RECOMMENDED FOR:

Lubricating and protecting moving parts such as doors, door hinges, rubber gaskets, weather stripping, exercise equipment and more.

NOT RECOMMENDED FOR:

- Use near heat, sparks or open flame.
- Some plastic surfaces as it may cause cloudiness on surface of some plastic surfaces.
- Applications where painting is required.
- Items that need to be handled (i.e. fishing rod, door handle) as it will lubricate the surface.

FEATURES & BENEFITS;

Feature	Benefits
Easy to use, convenient application.....	Aerosol format makes it easier to lubricate those hard to reach places such as locks, clocks etc.
Water resistant.....	Protects items from moisture and corrosion

DIRECTIONS:

Tools Typically Required

Kraft paper or other material to protect surrounding area.

Safety Precautions:

Well-ventilated area, wash hands after use.

Preparation:

Apply adhesive between 65°F (18°C) and 95°F (35°C). Shake well before using. Surfaces must be clean, dry and free of foreign materials. Protect finished surfaces. Turn spray tip so that the black dot is aligned with the nozzle.

Application:

Shake can before using. Point valve towards surface and spray from a distance of 8 to 10" (20 to 25 cm). Lightly spray surface to be treated. If using as a corrosion protection, wipe down surface after application. If used for lubricating moving parts, work parts back and forth after application.

Clean-up:

Clean valve of adhesive by turning can upside down and spraying for at least two seconds. Clean spray tip and excess wet and dried adhesive with paint thinner or turpentine.

STORAGE AND DISPOSAL:

Store above freezing. Do not store at temperatures above 120°F (50°C). Store at room temperature away from direct sunlight. Cans exposed to sunlight or heat may burst. Use an approved hazardous waste facility for disposal.

LABEL PRECAUTIONS:

Contains petroleum distillates. Do not use near heat, sparks or open flames. Do not expose to heat or store at temperatures above 120°F (50°C). High temperatures may cause container to burst. Use in a well-ventilated area. Avoid breathing spray, mist or vapor. If swallowed, do not induce vomiting, call a physician immediately. For skin contact, wash thoroughly with soap and water. If inhaled, remove to fresh air. If discomfort persists, call a physician. **KEEP OUT OF REACH OF CHILDREN.**

Refer to the Material Safety Data Sheet (MSDS) for further information

DISCLAIMER:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

TECHNICAL DATA:

Typical Uncured Physical Properties:		Typical Application Properties	
<u>Color:</u>	White Liquid	<u>Application Temperature:</u>	Between 65°F (18°C) and 95°F (35°C)
<u>Base:</u>	Silicone, Petroleum distillates, Liquefied petroleum	<u>Odor:</u>	Solvent (use in a well-ventilated area)
<u>VOC Content:</u>	20% by weight		
<u>Specific Gravity:</u>	0.90		
<u>Flash Point:</u>	20°F (-7°C)		